



LCS-2871-20

HD Conference Camera

- Full HD Image
- Super Silent Pan-Tilt
- Audio Input Interfaces
- Multiple Video Output Interfaces



20x Optical Zoom



MAIN FEATURES

1. Camera Performance and Image Quality

- High-Resolution Sensor: 1/2.8-inch 2.38MP sensor with 1920×1080 resolution, delivering up to 60 fps.
- Advanced Video and Audio Compression: Supports H.265/H.264 video and AAC, MP3, G.711A audio compression.

2. Compatibility and Connectivity

- Versatile Protocols Support: ONVIF, GB/T28181, RTSP, RTMP for streaming servers like Wowza, FMS, plus RTP multicast and VISCA control protocol.
- Control Protocols: Supports VISCA, PELCO-D, PELCO-P, with automatic protocol recognition.



3. System Integration and Motion Control

- Connection Interfaces: RS485 and RS232 support for cascading and easy installation.
- Precision Motor Control: High-precision stepper motors ensure smooth, noiseless pan-tilt movements.

SPECIFICATION

POWER PARAMETERS

Power Supply:	DC12V/1A
Power Consumption:	<12W

LENS PARAMETERS

Lens Optical Zoom:	20×Optical Zoom
Field Of View:	3.45° (Narrow Angle) To 60.04 ° (Wide Angle)
Aperture Range:	F1.8 – F2.9
Digital Zoom:	X10
Minimum Illumination:	0.5 Lux (F1.8, AGC ON)

PTZ PARAMETERS

Horizontal Rotation:	-170° To +170°
Vertical Tilt:	-30° To +90°
Horizontal Control Speed:	From 0.1°/s to 100°/s
Vertical Control Speed:	From 0.1°/s to 30°/s
Preset Speed:	Horizontal: 60°/s Vertical: 30°/s
Number Of Presets:	Users Can Set Up To 255 Presets Position (10 Presets For Remote Controller)


MECHANICAL&ENVIRONMENT PROPERTIES

Mounting Method:	Bracket Mount
Installation Environment:	Indoor Locations
Operating Temperature:	-10°C~+60°C
Operating Humidity:	20%~80%
Dimensions:	258×172×169mm
Product Weight:	1.46Kg
Warranty:	2 Years

ACCESSORIES


1×Remote Control
1×Power Adapter (Optional)
1×Formal Support (Wall Mounted) (Optional)
1×Flip Bracket (Lifting) (Optional)
1×Rubber Pad
1×RS232 Serial Cable
4×Countersunk Screw (M3*6)
1×Half Round Screw (M6*10)
1×M3*5 Screw
1×2P Euro Block
1×USB 2.0 Cable
1×Quick Installation Guide
1×Warranty Card & Certification Card

INTERFACE DESCRIPTION




APPLICATIONS

The Conference central unit LCS-5203L support to connect with chairman unit and delegate unit for local conference , also it provide audio output interface to realize local conference sound amplification. Meanwhile , it support to connect with HD conference camera for video tracking of conference presentation.




DIMENSION DRAWING




INSTALLATION

Bracket Installation Steps



Bracket Installation Steps (Ceiling Mount)



INSTALLATION

