



LCS-5252D

Wireless Digital Conference Delegate Unit

- Video Tracking
- 4.3" Touchscreen
- High-Fidelity Microphone
- Supports Type-C charging with charging base



Type-C/Magnetic
charging

4.3-Inch
Touch Screen

Voting/
Attendance

2.4-5.8G Hz

MAIN FEATURES

▲ Intercom and Communication

- **Directory Access:** Can access the intercom server directory for initiating IP intercom functions..
- **IP Address Utilization:** Enables communication using IP addresses or directory listings.

▲ Design and Audio Quality

- **Acoustic Chamber:** Microphone stem features a special design for aesthetics and sound quality.
- **High-Fidelity Microphone:** 14mm diameter super-cardioid gold-plated condenser microphone for long-distance sound capture.
- **Ergonomic Base:** Meticulously designed for user comfort style.
- **High-Resolution Touchscreen:** 4.3-inch full-color display with 480*480 resolution for an intuitive user interface.

▲ Technical Advantages

- **Digital Signal Transmission:** Offers strong resistance to interference.
- **Status Indicators:** Speech status indicator light on the microphone stem and a light ring on the base.
- **Wireless Connectivity:** Utilizes WiFi for seamless communication
- **Video Tracking:** Incorporates video tracking for enhanced meeting dynamics.
- **Sign-In and Voting:** Facilitates conference sign-in, voting, and decision-making with real-time result display.

SPECIFICATION

POWER PARAMETERS

Power Supply: Lithium Battery (4000mAh)

Power Consumption: ≤3W

AUDIO PARAMETERS

Audio Codec: MP3/PCM/ADPCM

Audio Sampling Rate ,Bit Rate: 8Khz-44.1Khz,16bit,8Kbps-320k bps

SNR: ≥83dB

Frequency Response: 40Hz-18KHz

MECHANICAL & ENVIRONMENTAL PROPERTIES

Mounting Method: Desktop

Installation Environment: Dry Indoor Locations

Display: 4.3 Inch Capacitive Touch Screen

Product Color: Black

Microphone Head: 14mm Diameter Gold-Plated Capacitive Microphone

Directional: Supercardioid

Shell Material: ABS/Aluminum Alloy

Working Temperature: 0°C~+45°C

Working Humidity: ≤90%, No Condensation

Product Dimensions: 220×98.8×107.6 (mm)

Warranty: 2 Years

ACCESSORIES


1×Quick Installation Guide

1×Quality Certificate


1×Warranty Card

INTERFACE DESCRIPTION


[Front Panel]



[Rear Panel]



CONNECTION DIAGRAM



DIMENSIONAL DRAWING

