

XC-9242V

Network Emergency Call Module


SPON IP Outdoor Video Intercom Station XC-9242V is designed for outdoor environment use, stable and durable. This station is typically used as a communication, or emergency point and connects directly to the IP network, making it easy to deploy anywhere and at any distance.

SIP Onvif IPX5 HD1080P

MAIN FEATURES


1. Design and Communication

- Durable, all-metal shell with IPX5 waterproof rating and resistance to violence.
- One-touch call function for full-duplex intercom, pre-set via server.
- Built-in 10W speaker and microphone for hands-free calling and broadcasting.



3. Connectivity and Security Features

- SIP protocol compatibility for independent VOIP phone system registration.
- ONVIF protocol compliance for direct connection to mainstream NVRs and storage devices for synchronized audio-video recording.
- Two alarm inputs for connecting external emergency buttons.
- DC12V/500mA controlled power output for driving a strobe light.
- Standard RJ45 interface for network flexibility and Ethernet accessibility.



SPECIFICATION

POWER PARAMETERS

Power Supply: DC 24V/2.7A
Amplifier Power Output: 2*20W/8Ω

AUDIO & VIDEO PARAMETERS

Audio Codec: WAV, PCM, ADPCM
Audio Sampling & Bit Rate: 8kHz~44.1kHz, 16bit, 8kbps~320kbps
Built-In Speaker: 10W, 8Ω
SNR: Speaker Output≥90dB
Amplifier Output≥84dB
Recording Output≥80dB
Built-In Camera: 1/3" CMOS
Video Coding: VGA/720P/1080P

NETWORK PARAMETERS

Network I/F: 10BASE-T/100BASE-TX RJ45
Network Protocol: TCP/IP, UDP, ARP, ICMP, IGMP, SIP, HTTP
Configuration Method: Web Interface Or DevConfig Tool.


MECHANICAL & ENVIRONMENT PROPERTIES

Mounting Method:	Embedded-Mounted
Installation Environment:	Outdoor Locations
Operating Temperature:	-30°C~+55°C
Operating Humidity:	≤90% RH Non-Condensing
Shell Material:	Stainless Steel
Color:	Silver
Product Dimensions:	360×252×74mm
Protection Level:	IPX5
Product Warranty:	2 Years Limited


Accessories

1×Waterproof Connector
3×Plastic Expansion Sleeve(M8*40)
2×Terminal(3.81-4P)
4×Terminal(3.81-3P)
4×Hexagon Socket Screw(M8*18)
1×Power Adaptor(DC24V/2.7A)
3×Half Round Head Phillips Screw(M6*40)
1×Quick Installation Guide
1×Certificate And Warranty Card

PORTS DESCRIPTION



CONNECTION DIAGRAM



CASE

