


# Milesight

# 4K Pro NVR 5000 Series

NDAA 

4K



## DATASHEET

## KEY FEATURES

- NDAA Compliance (The fully NDAA-compliant products are well suited for government, defense and a range of projects subject to the NDAA.)
- 8/16-CH Network Video Input (Up to 8/16 channels IP cameras can be connected.)
- Dual Stream Recording (Supporting Primary Stream and Secondary Stream recording simultaneously.)
- Auto Backup (The latest 24 hours' video will be automatically backed up to USB Port Devices or NAS after setting up the backup.)


## Power Decoding Capacity & Flexible Storage Options

- The 4K NVR is equipped with solid 4K decoding and display capabilities and maximum support simultaneous viewing of 6\*1080P or 12\*720P network cameras.
- Providing flexible storage options including HDD and NAS to address the needs for versatile storage.




## AI Video Analytics & POS Integration

- All-in-one to Manage AI & ANPR:
  - VCA Function focus on human and vehicle detection.
  - People Counting provides high-accuracy data and statistic reports.
  - Face Detection function supports attribute recognition.
  - Enterprise ANPR Management makes it easy to monitor traffic.
- POS machine information can be transferred to and displayed on the NVR.



## Reliability

- ANR can store video data on the camera storage card when network between IPC and NVR is disconnected and retransfer the recorded video to NVR after network recovers.



## Flexible Structure

- U-Rack Standard supported.
- A whole array of ports provides all necessary features for effective surveillance.



# 4K Pro NVR 5000 Series



Model		MS-N5008-E	MS-N5016-E
Video/Audio Input	Network Video Input	8-CH	16-CH
	Bandwidth	80Mbps	
Video/Audio Output	Incoming	50Mbps	
	HDMI Output	1-CH, Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	HDMI Supports Audio Output
	VGA Output	1-CH, Resolution: 1920x1080/60Hz, 1920x1080/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
	Dual Stream	Support	
	Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/D1/VGA/CIF/QCIF	*The recommended parameters are theoretical values only. Actual performance may vary depending on the usage environment, the number of connected cameras, and their models. *Resolutions with width or height >4096 not supported for decoding.
Video/Audio Compression	Synchronous Playback	1*(30fps @8MP), 2*(30fps @6MP), 2*(30fps @5MP), 3*(30fps @4MP), 4*(30fps @3MP), 6*(30fps @1080P), 8*(30fps @720P)	1*(30fps @8MP), 2*(30fps @6MP), 2*(30fps @5MP), 3*(30fps @4MP), 4*(30fps @3MP), 6*(30fps @1080P), 12*(30fps @720P)
	Video Compression	H.264/H.264	
	Audio Compression	G.711/AAC/G.722/G.726	
Storage	Sample Rate	8KHz/16KHz	
	SATA	2*SATA HDD(3.5")	
Recording Management	Capacity	Up to 10TB capacity for each HDD	
	Recording Type	Continuous, Event (Motion Detection, Alarm, VCA, Smart Analysis)	
	Snapshot Type	N/A	Continuous, Event (Motion Detection, Alarm, VCA, Smart Analysis)
Backup	Playback Type	General Playback, Event Playback, Tag Playback, Split Playback, Picture Playback	
	Backup	Video Backup, Image Backup	
Network	Protocol	IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, NTP, SNTP, SMTP, SNMP, UPnP, NFS	
External Interface	Network Interface	1*RJ45 10/100/1000Mbps	
	USB Interface	2*USB 2.0	
	Audio Input/Output	1*RCA/1*RCA	
	Alarm Input/Output	4-CH/1-CH	
General	Compatibility	ONVIF, API	
	Advanced Function	ANR	
	ANPR	Support	
	Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, People Counting, Object Left, Object Removed	
	Keyboard Control	Milesight Keyboard (MS-K01)	
	Power Supply	DC 12V 50Hz~60Hz	
	Consumption	≤3W(Without HDD)	≤4W(Without HDD)
	Working Conditions	Temperature: -10°C~55°C / Humidity: 10%~90%	Temperature: -10°C~55°C / Humidity: 10%~90%
	Dimensions	Rack Mountable Chassis (1.0U Standard) 380mm(W)X317.6mm(D)X51.8mm(H)	
	Weight	1.9Kg	
	Warranty	3/5 Years	



V8.03

# 4K Pro NVR 5000 Series




## Interfaces

MS-N5008-E/MS-N5016-E




1. Run Indicator 2. HDD Indicator 3. Power Indicator 4. USB 5. Alarm In/Out  
9. Ethernet Port 10. Power 11. Power Button 12. GND 13. Audio In 14. VGA

## Structure Diagrams



Units: mm

## Naming Convention



**Milesight** | [www.milesight.com](http://www.milesight.com)

Contact Us: [sales@milesight.com](mailto:sales@milesight.com) [support@milesight.com](mailto:support@milesight.com)

Add: 220 NE 51st Street, Oakland Park, Florida 33334, USA  
Tel: +1-800-561-0485

Add: 925, Anyang SK V1 Center, LS-ro 116beon-gil, Dongan-gu, Anvang-si, Korea  
Tel: +82-31-990-7732

Add: Building C09, Software Park Phase III, Xiamen 361024, Fujian, China  
Tel: +86-592-5922772

