

AI Motorized Pro Bullet Network Camera



Motorized Lens

IP67



DATASHEET

Key Features

- NDAA Compliance (The fully NDAA-compliant products are well suited for government, defense and a range of projects subject to the NDAA.)
- Precision Imaging Technology (Powered by P-Iris and a high-performance Day-Night Focus Lens to deliver stunning image clarity.)
- 140dB Super WDR (Excellent performance even when the ratio of the luminosity of brightest and darkest is up to 140dB.)
- Up to 4K@60fps (Camera can easily capture fast-moving objects smoothly with no latency.)
- Hybrid Zoom (Combines optical and digital zoom to capture detailed images.)
- 1TB Edge Storage (Supports external microSD/SDHC/SDXC cards up to 1TB for ultra-large on-device storage.)
- Versatile Interfaces (Integrates DC 10V~28V power, PoE, audio, and alarm interfaces neatly within the base, making it adaptable to various environments.)

Smarter Detection, Greater Accuracy

Focused on person and vehicle classification using deep learning, the full suite of AI VCA 2.0 delivers ultra-low false alarm rates, supports longer-range detection, and ensures robust physical security. Meanwhile, MSense is purpose-built to address diverse vertical applications, delivering tailored intelligence and enhanced adaptability.




Crystal-Clear Video Streaming

Delivers 4K ultra-high-definition resolution at up to 60fps, and supports Digital Image Stabilization (DIS) for smooth, stable video. Quad-Stream reduces bandwidth and storage usage while dedicating each stream for recording, live view, mobile access, or AI processing.




Superior Low-light Performance

Equipped with a Sony STARVIS 2, 1/1.8" large sensor and Day-Night Focus Lens, the camera delivers ultra-clear, superior images down to 0.0008Lux@F1.2 (Color). Powered by AI ISP, it further enhances image quality by reducing noise and improving clarity in the darkest environments.



Efficient & Simple Installation

Milesight's camera integrates an all-in-one junction box with multiple interfaces, IP67 protection and a 1TB SD card slot. This ensures easy installation, dependable durability, and versatile performance within a rugged structure.



AI Motorized Pro Bullet Network Camera



	Model	MS-C2962-RFPG1 (2MP)	MS-C2962-RFIPG1 (2MP)
Camera	Image Sensor	1/2.8" Progressive Scan CMOS	
	Min. Illumination	Color: 0.003Lux@F1.4, B/W: 0Lux with IR on	Color: 0.001Lux@F1.2, B/W: 0Lux with IR on
	WDR	140dB Super WDR	
	Shutter Time	1/100000s~1s	
	Day/Night Mode	Day / Night / Auto / Customize / Schedule	
	DORI Distance	D: 47~152m O: 18.5~59.8 R: 9.3~29.9m I: 4.7~14.9m	D: 47.8~134m O: 18.8~52.8 R: 9.5~26.4m I: 4.7~13.2m
	S/N	>55dB	
Illuminator	Illuminator Number	4	
	IR Wave Length	850nm	
	Illumination Distance	Up to 60m	Up to 65m
	Illuminator On/Off Control	Auto / Manual	
Lens	Lens	Motorized 2.7mm~13.5mm@F1.4	Motorized 2.7mm~13.5mm@F1.2
	Field of View	H103.4° ~ H31.1° / D121.2° ~ D35.9° / V55.5° ~ V17.4°	H112.7° ~ H37.2° / D133.5° ~ D42.8° / V58.5° ~ V20.8°
	Close Focus Distance	W: 1m, T: 1m	
	Camera Angle Adjustment	Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotation: 0° ~ 360°	
	Mount	Φ 14	Φ 17
	Focus Control	Auto / Manual	
	Aperture	Max.F1.4	Max.F1.2
Video	Iris Type	Fixed	P-Iris
	Iris Control	NA	Auto / Manual
	Max. Image Resolution	1920x1080	
	Primary Stream	60Hz: 60fps@(1920x1080, 1280x960, 1280x720) 50Hz: 50fps@(1920x1080, 1280x960, 1280x720)	
	Secondary Stream	60Hz: 60fps@(704x576, 640x480, 640x360), 50Hz: 50fps@(704x576, 640x480, 640x360)	
	Tertiary Stream	60Hz: 30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360) 50Hz: 25fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360)	
	Quaternary Stream	60Hz: 10fps@(1280x720), 30fps@(704x576, 640x480, 640x360) 50Hz: 10fps@(1280x720), 25fps@(704x576, 640x480, 640x360)	
Video	Video Compression	H.265+/H.265 (HEVC)/H.264+/H.264/MJPEG	
	Video Bit Rate	16Kbps ~ 16Mbps (CBR/VBR Adjustable)	

AI Motorized Pro Bullet Network Camera



Image	Privacy Masking	Up to 8 Areas (Mask Area and Mosaic Area are optional)
	ROI	Up to 8 areas
	Image Setting	Brightness / Contrast / Saturation / Sharpness
	Image Rotation	Off, Rotating 180°, Flip Horizontal, Flip Vertical, Clockwise 90°, Anticlockwise 90°
	Image Enhancement	BLC, HLC, 2D DNR, 3D DNR, AGC, Defog, AWB, Deblur, Anti-flicker, LDC, DIS
	Hybrid Zoom	Up to 40X
Network	Network Storage	NAS (Support NFS, SMB/CIFS), ANR
	Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, LLDP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, VPN, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL, TLS 1.2
Interface	Ethernet	1*RJ45 10M/100M Ethernet Port
	Audio I/O	1/1
	Alarm I/O	1/1
Audio	Audio Compression	G.711/AAC/G.722/G.726
	Audio Sampling Rate	8/16/32/44.1/48KHz
	Audio Bit Rate	16~256kbps
Intelligent Analytics	Video Analysis	VCA 2.0: Intrusion Detection, Region Entrance, Region Exiting, Advanced Motion Detection, Line Crossing, Loitering, Object Left, Object Removed
	Attribute Extraction	Simultaneously detect up to 50 targets and capture humans and vehicles in real time. Recognize attributes including Upper and Lower Clothing Color, Hat, and Vehicle Types (Bicycle, Car, Motorcycle, Bus, Truck, E-scooter).
	Face Detection & Face	Detect and capture faces, get real-time snapshots.
	Attribute Recognition	The attributes include Age, Gender, Glasses, Mask and Cap.
	Object Counting & Report	Count the number of objects crossing the line, optionally human and vehicle. Support regional people counting for up to 4 detection areas.
	Heat Map	The built-in statistical behavior analysis enables you to identify the busiest areas within the environment
	Hard Hat Detection	Detect whether individuals are wearing safety hats. Trigger an alarm when a person is identified without a hard hat.
	Privacy Protection	Automatically detect faces or human bodies in the video stream and overlay mosaic effects. Supported on Primary Stream/Secondary Stream, Compatible with H.265/H.264 formats.
	Fall Detection	Detect a person's fall and trigger an alarm to alert others for timely assistance.
	Violence Detection	Identify violent behavior and trigger an alarm to alert others to intervene or prevent the action.

AI Motorized Pro Bullet Network Camera



Event	One-Click Disarm	Support
	Basic Event	Motion Detection, Tamper Detection, Audio Alarm, External Input, External Output etc.
	Exception	Network Disconnection, IP Address Conflict, Record Failed, SD Card Full, SD Card Uninitialized, SD Card Error, No SD Card, etc.
	Event Action	FTP Upload Record, SMTP Upload Record, SD Card Record, Snapshot, External Output, Play Audio, SIP Phone, HTTP Notification, etc.
System	Watermark	Support
	Storage	Support Micro SD/SDHC/SDXC Card Local Storage, up to 1TB
	SIP/VoIP Support	Yes, Voice & Video-over-IP
	System Compatibility	ONVIF Profile G & M & S & T, One API
General	Working Temperature	-40°C~60°C
	Working Humidity	0~95% RH (Non-condensing)
	Power Supply	PoE (802.3af) / DC 10V~DC 28V
	Power Consumption	Min.: 3W (DC), 3.9W (PoE) 24 Hour Average: 4.5W (DC), 5.6W (PoE) Max.: 6.8W (DC), 8.4W (PoE) Max.: 7.8W (DC), 9.6W (PoE)
	Surge Protection	4KV
	Net Weight	Approx. 1.3kg
	Gross Weight	Approx. 2.1kg
	Dimensions	134mm X 126mm X 285mm
	Warranty	3 Years / 5 Years (Optional)
	EMC	CE-EMC (EN 55032, EN 55035), FCC (PART 15B)
Certifications	Safety	CE-LVD (EN IEC 62368-1)
	Environment	CE-ROHS (Directive (EU) 2015/863 amending 2011/65/EU)
	Protection	IP67

AI Motorized Pro Bullet Network Camera



	Model	MS-C5362-RFPG1 (5MP)	MS-C5362-RFIPG1 (5MP)
Camera	Image Sensor	1/2.8" Progressive Scan CMOS	
	Min. Illumination	Color: 0.006Lux@F1.4, B/W: 0Lux with IR on	Color: 0.004Lux@F1.2, B/W: 0Lux with IR on
	WDR	120dB Super WDR	
	Shutter Time	1/100000s~1s	
	Day/Night Mode	Day / Night / Auto / Customize / Schedule	
	DORI Distance	D: 84.6m ~ 273m O: 33.9m ~ 108m R: 16.6m ~ 53.8m I: 8.4m~26.9m	D: 86.1m ~ 242m O: 33.9m ~ 95.1m R: 16.9m ~ 47.5m I: 8.5m~23.8m
	S/N	>55dB	
Illuminator	Illuminator Number	4	
	IR Wave Length	850nm	
	Illumination Distance	Up to 60m	
	Illuminator On/Off Control	Auto / Manual	
Lens	Lens	Motorized 2.7mm~13.5mm@F1.4	Motorized 2.7mm~13.5mm@F1.2
	Field of View	H93.8° ~ 32.1° / D121.5° ~ 44.7° / V68.2°~22.2°	H93.7° ~ 32.9° / D121.1° ~ 40.7° / V68.2°~24.7°
	Close Focus Distance	W:0.5m, T:1m	W:1m, T:1m
	Camera Angle Adjustment	Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotation: 0° ~ 360°	
	Mount	Φ14	Φ17
	Focus Control	Auto/Manual	
	Aperture	Max.F1.4	Max.F1.2
	Iris Type	Fixed	P-Iris
	Iris Control	NA	Auto / Manual
Video	Max. Image Resolution	2592x1944	
	Primary Stream	60Hz: 60fps@(2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720) 50Hz: 50fps@(2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720)	
	Secondary Stream	60Hz: 60fps@(704x576, 640x480, 640x360), 50Hz: 50fps@(704x576, 640x480, 640x360)	
	Tertiary Stream	60Hz: 30fps@(2048x1536,1600x1200,1920x1080, 1280x720, 704x576, 640x480, 640x360) 50Hz: 25fps@(2048x1536, 1600x1200, 1920x1080, 1280x720, 704x576, 640x480, 640x360)	
	Quaternary Stream	60Hz: 10fps@(1280x720), 30fps@(704x576, 640x480, 640x360) 50Hz: 10fps@(1280x720), 25fps@(704x576, 640x480, 640x360)	
	Video Compression	H.265+/H.265 (HEVC)/H.264+/H.264/MJPEG	
	Video Bit Rate	16Kbps ~ 16Mbps (CBR/VBR Adjustable)	

AI Motorized Pro Bullet Network Camera



Image	Privacy Masking	Up to 8 Areas (Mask Area and Mosaic Area are optional)
	ROI	Up to 8 Areas
	Image Setting	Brightness / Contrast / Saturation / Sharpness
	Image Rotation	Off, Rotating 180°, Flip Horizontal, Flip Vertical, Clockwise 90°, Anticlockwise 90°
	Image Enhancement	BLC, HLC, 2D DNR, 3D DNR, AGC, Defog, AWB, Deblur, Anti-flicker, LDC, DIS
	Hybrid Zoom	Up to 40X
Network	Network Storage	NAS (Support NFS, SMB/CIFS), ANR
	Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, LLDP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, VPN, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL, TLS 1.2
Interface	Ethernet	1*RJ45 10M/100M Ethernet Port
	Audio I/O	1/1
	Alarm I/O	1/1
Audio	Audio Compression	G.711/AAC/G.722/G.726
	Audio Sampling Rate	8/16/32/44.1/48KHz
	Audio Bit Rate	16~256kbps
Intelligent Analytics	Video Analysis	VCA 2.0: Intrusion Detection, Region Entrance, Region Exiting, Advanced Motion Detection, Line Crossing, Loitering, Object Left, Object Removed
	Attribute Extraction	Simultaneously detect up to 50 targets and capture humans and vehicles in real time. Recognize attributes including Upper and Lower Clothing Color, Hat, and Vehicle Types (Bicycle, Car, Motorcycle, Bus, Truck, E-scooter).
	Face Detection & Face	Detect and capture faces, get real-time snapshots.
	Attribute Recognition	The attributes include Age, Gender, Glasses, Mask and Cap.
	Object Counting & Report	Count the number of objects crossing the line, optionally human and vehicle. Support regional people counting for up to 4 detection areas.
	Heat Map	The built-in statistical behavior analysis enables you to identify the busiest areas within the environment.
	Hard Hat Detection	Detect whether individuals are wearing safety hats. Trigger an alarm when a person is identified without a hard hat.
	Privacy Protection	Automatically detect faces or human bodies in the video stream and overlay mosaic effects. Supported on Primary Stream / Secondary Stream, Compatible with H.265/H.264 formats.
	Fall Detection	Detect a person's fall and trigger an alarm to alert others for timely assistance.
	Violence Detection	Identify violent behavior and trigger an alarm to alert others to intervene or prevent the action.

AI Motorized Pro Bullet Network Camera



Event	One-Click Disarm	Support
	Basic Event	Motion Detection, Tamper Detection, Audio Alarm, External Input, External Output etc.
	Exception	Network Disconnection, IP Address Conflict, Record Failed, SD Card Full, SD Card Uninitialized, SD Card Error, No SD Card, etc.
	Event Action	FTP Upload Record, SMTP Upload Record, SD Card Record, Snapshot, External Output, Play Audio, SIP Phone, HTTP Notification, etc.
System	Watermark	Support
	Storage	Support Micro SD/SDHC/SDXC Card Local Storage, up to 1TB
	SIP/VoIP Support	Yes, Voice & Video-over-IP
	System Compatibility	ONVIF Profile G & M & S & T, One API
General	Working Temperature	-40°C~60°C
	Working Humidity	0~95% RH (Non-condensing)
	Power Supply	PoE (802.3af) / DC 10V~DC 28V
	Power Consumption	Min.: 3.2W (DC), 4.2W (PoE) 24 Hour Average: 4.7W (DC), 5.9W (PoE) Max.: 7.8W (DC), 9.4W (PoE)
	Surge Protection	4KV
	Net Weight	Approx. 1.3kg
	Gross Weight	Approx. 2.1kg
	Dimensions	134mm X 126mm X 285mm
	Warranty	3 Years / 5 Years (Optional)
Certifications	EMC	CE-EMC (EN 55032, EN 55035), FCC (PART 15B)
	Safety	CE-LVD (EN IEC 62368-1)
	Environment	CE-ROHS (Directive (EU) 2015/863 amending 2011/65/EU)
	Protection	IP67

*The tested results may vary due to environmental conditions and device differences.

AI Motorized Pro Bullet Network Camera



	Model	MS-C8162-RFPG1 (8MP)	MS-C8162-RFIPG1 (8MP)	
Camera	Image Sensor	1/2.8" Progressive Scan CMOS		
	Min. Illumination	Color: 0.009Lux@F1.4, B/W: 0Lux with IR on	Color: 0.006Lux@F1.2, B/W: 0Lux with IR on	
	WDR	120dB Super WDR		
	Shutter Time	1/100000s~1s		
	DORI Distance	D: 95.7m ~ 268m O: 37.6m ~ 106m R: 18.8m ~ 52.8m I: 9.5m ~ 26.4m	D: 93.9m ~ 304m O: 37m ~ 120m R: 18.5m ~ 59.8m I: 9.3m ~ 29.9m	
	Day/Night Mode	Day / Night / Auto / Customize / Schedule		
	S/N	>55dB		
Illuminator	Illuminator Number	4		
	IR Wave Length	850nm		
	Illumination Distance	Up to 60m		
	Illuminator Control	Auto / Manual		
Lens	Lens	Motorized 2.7mm~13.5mm@F1.4	Motorized 2.7mm~13.5mm@F1.2	
	Field of View	H100.2° ~ H30.7° / D117.1° ~ D35.5° / V53.2° ~ V17.1°	H100.2° ~ H27° / D117.9° ~ D31.1° / V51.9° ~ V15.1°	
	Close Focus Distance	W: 1m, T: 1m		
	Camera Angle Adjustment	Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotation: 0° ~ 360°		
	Mount	Φ14	Φ17	
	Focus Control	Auto / Manual		
	Aperture	Max.F1.4	Max.F1.2	
	Iris Type	Fixed	P-Iris	
Video	Iris Control	NA	Auto / Manual	
	Max. Image Resolution	3840x2160		
	Primary Stream	60Hz: 60fps@(3840x2160, 3072x2048, 2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720) 50Hz: 50fps@(3840x2160, 3072x2048, 2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720)		
	Secondary Stream	60Hz: 60fps@(704x576, 640x480, 640x360), 50Hz: 50fps@(704x576, 640x480, 640x360)		
	Tertiary Stream	60Hz: 30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360) 50Hz: 25fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360)		
	Quaternary Stream	60Hz: 10fps@(1280x720), 30fps@(704x576, 640x480, 640x360) 50Hz: 10fps@(1280x720), 25fps@(704x576, 640x480, 640x360)		
	Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG		
	Video Bit Rate	16Kbps ~ 16Mbps(CBR/VBR Adjustable)		

AI Motorized Pro Bullet Network Camera



Image	Privacy Masking	Up to 8 Areas (Mask Area and Mosaic Area are optional)
	ROI	Up to 8 Areas
	Image Setting	Brightness / Contrast / Saturation / Sharpness
	Image Rotation	Off, Rotating 180°, Flip Horizontal, Flip Vertical, Clockwise 90°, Anticlockwise 90°
	Image Enhancement	BLC, HLC, 2D DNR, 3D DNR, AGC, Defog, AWB, Deblur, Anti-flicker, LDC, DIS
	Hybrid Zoom	Up to 40X
Network	Network Storage	NAS (Support NFS, SMB/CIFS), ANR
	Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, LLDP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, VPN, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL, TLS 1.2
Interface	Ethernet	1*RJ45 10M/100M Ethernet Port
	Audio I/O	1/1
	Alarm I/O	1/1
Audio	Audio Compression	G.711/AAC/G.722/G.726
	Audio Sampling Rate	8/16/32/44.1/48KHz
	Audio Bit Rate	16~256kbps
Intelligent Analytics	Video Analysis	VCA 2.0: Intrusion Detection, Region Entrance, Region Exiting, Advanced Motion Detection, Line Crossing, Loitering, Object Left, Object Removed
	Attribute Extraction	Simultaneously detect up to 50 targets and capture humans and vehicles in real time. Recognize attributes including Upper and Lower Clothing Color, Hat, and Vehicle Types (Bicycle, Car, Motorcycle, Bus, Truck, E-scooter).
	Face Detection & Face	Detect and capture faces, get real-time snapshots.
	Attribute Recognition	The attributes include Age, Gender, Glasses, Mask and Cap.
	Object Counting & Report	Count the number of objects crossing the line, optionally human and vehicle. Support regional people counting for up to 4 detection areas.
	Heat Map	The built-in statistical behavior analysis enables you to identify the busiest areas within the environment.
	Hard Hat Detection	Detect whether individuals are wearing safety hats. Trigger an alarm when a person is identified without a hard hat.
	Privacy Protection	Automatically detect faces or human bodies in the video stream and overlay mosaic effects. Supported on Primary Stream / Secondary Stream, Compatible with H.265/H.264 formats.
	Fall Detection	Detect a person's fall and trigger an alarm to alert others for timely assistance.
	Violence Detection	Identify violent behavior and trigger an alarm to alert others to intervene or prevent the action.

AI Motorized Pro Bullet Network Camera



Event	One-Click Disarm	Support
	Basic Event	Motion Detection, Tamper Detection, Audio Alarm, External Input, External Output etc.
	Exception	Network Disconnection, IP Address Conflict, Record Failed, SD Card Full, SD Card Uninitialized, SD Card Error, No SD Card, etc.
	Event Action	FTP Upload Record, SMTP Upload Record, SD Card Record, Snapshot, External Output, Play Audio, SIP Phone, HTTP Notification, etc.
System	Watermark	Support
	Storage	Support Micro SD/SDHC/SDXC Card Local Storage, up to 1TB
	SIP/VoIP Support	Yes, Voice & Video-over-IP
	System Compatibility	ONVIF Profile G & M & S & T, One API
General	Working Temperature	-40°C~60°C
	Working Humidity	0~95% RH (Non-condensing)
	Power Supply	PoE (802.3af) / DC 10V~DC 28V
	Power Consumption	Min.: 4.2W (DC), 5.2W (PoE) 24 Hour Average: 5.7W (DC), 7W (PoE)
	Surge Protection	Max.: 7.5W (DC), 9.2W (PoE) Max.: 8W (DC), 9.6W (PoE)
	Net Weight	4KV Approx. 1.3kg
	Gross Weight	Approx. 2.1kg
	Dimensions	134mm X 126mm X 285mm
	Warranty	3 Years / 5 Years (Optional)
Certifications	EMC	CE-EMC (EN 55032, EN 55035), FCC (PART 15B)
	Safety	CE-LVD (EN IEC 62368-1)
	Environment	CE-ROHS (Directive (EU) 2015/863 amending 2011/65/EU)
	Protection	IP67

*The tested results may vary due to environmental conditions and device differences.

AI Motorized Pro Bullet Network Camera



	Model	MS-C4462-RFIPG1 (4MP)	MS-C8262-RFIPG1 (8MP)
Camera	Image Sensor	1/1.8" Progressive Scan CMOS	
	Min. Illumination	Color: 0.001Lux@F1.2, B/W: 0Lux with IR on	Color: 0.0008Lux@F1.2, B/W: 0Lux with IR on
	WDR	140dB Super WDR	120dB Super WDR
	Shutter Time	1/100000s~1s	
	DORI Distance	D: 69.3m ~ 149m O: 27.3m ~ 58.7m R: 13.6m ~ 29.3m I: 6.9m ~ 14.7m	D: 98.5m ~ 212m O: 38.8m ~ 83.4m R: 19.4m ~ 41.7m I: 9.7m ~ 20.8m
	Day/Night Mode	Day / Night / Auto / Customize / Schedule	
	S/N	>55dB	
Illuminator	Illuminator Number	4	
	IR Wave Length	850nm	
	Illumination Distance	Up to 70m	
	Illuminator Control	Auto / Manual	
Lens	Lens	Motorized 2.8mm~12mm@F1.2	
	Field of View	H111.6° ~ H47.5° / D129.4° ~ D54.5°/V58.8°~V26.7°	H105.3° ~ H46.8° / D122.6° ~ D53.9°/V55.6° ~ V26.2°
	Close Focus Distance	W: 1m, T: 1.5m	
	Camera Angle Adjustment	Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotation: 0° ~ 360°	
	Mount	Φ17	
	Focus Control	Auto / Manual	
	Aperture	Max.F1.2	
	Iris Type	P-Iris	
Video	Iris Control	Auto / Manual	
	Max. Image Resolution	2688 x 1520	3840x2160
	Primary Stream	60Hz: 60fps@(2688x1520, 2304x1296, 1920x1080, 1280x720) 50Hz: 50fps@(2688x1520, 2304x1296, 1920x1080, 1280x720)	60Hz: 60fps@(3840x2160, 3072x2048, 2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720) 50Hz: 50fps@(3840x2160, 3072x2048, 2592x1944, 2592x1520, 2048x1536, 1920x1080, 1280x960, 1280x720)
	Secondary Stream	60Hz: 60fps@(704x576, 640x480, 640x360), 50Hz: 50fps@(704x576, 640x480, 640x360)	
	Tertiary Stream	60Hz: 30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360) 50Hz: 25fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360)	
	Quaternary Stream	60Hz: 10fps@(1280x720), 30fps@(704x576, 640x480, 640x360) 50Hz: 10fps@(1280x720), 25fps@(704x576, 640x480, 640x360)	
	Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG	
	Video Bit Rate	16Kbps ~ 16Mbps(CBR/VBR Adjustable)	

AI Motorized Pro Bullet Network Camera



Image	AI ISP	NA	Support
	Privacy Masking	Up to 8 Areas (Mask Area and Mosaic Area are optional)	
	ROI	Up to 8 areas	
	Image Setting	Brightness / Contrast / Saturation / Sharpness	
	Image Rotation	Off, Rotating 180°, Flip Horizontal, Flip Vertical, Clockwise 90°, Anticlockwise 90°	
	Image Enhancement	BLC, HLC, 2D DNR, 3D DNR, AGC, Defog, AWB, Deblur, Anti-flicker, LDC, DIS	
Network	Hybrid Zoom	Up to 32X	
	Network Storage	NAS (Support NFS, SMB/CIFS), ANR	
	Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, LLDP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, VPN, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL, TLS 1.2	
Interface	Ethernet	1*RJ45 10M/100M Ethernet Port	
	Audio I/O	1/1	
	Alarm I/O	1/1	
Audio	Audio Compression	G.711/AAC/G.722/G.726	
	Audio Sampling Rate	8/16/32/44.1/48KHz	
	Audio Bit Rate	16~256kbps	
Intelligent Analytics	Video Analysis	VCA 2.0: Intrusion Detection, Region Entrance, Region Exiting, Advanced Motion Detection, Line Crossing, Loitering, Object Left, Object Removed	
	Attribute Extraction	Simultaneously detect up to 50 targets and capture humans and vehicles in real time. Recognize attributes including Upper and Lower Clothing Color, Hat, and Vehicle Types (Bicycle, Car, Motorcycle, Bus, Truck, E-scooter).	
	Face Detection & Face	Detect and capture faces, get real-time snapshots.	
	Attribute Recognition	The attributes include Age, Gender, Glasses, Mask and Cap.	
	Object Counting & Report	Count the number of objects crossing the line, optionally human and vehicle. Support regional people counting for up to 4 detection areas.	
	Heat Map	The built-in statistical behavior analysis enables you to identify the busiest areas within the environment	
	Hard Hat Detection	Detect whether individuals are wearing safety hats. Trigger an alarm when a person is identified without a hard hat.	
	Privacy Protection	Automatically detect faces or human bodies in the video stream and overlay mosaic effects. Supported on Primary Stream / Secondary Stream, Compatible with H.265/H.264 formats.	
	Fall Detection	Detect a person's fall and trigger an alarm to alert others for timely assistance.	
	Violence Detection	Identify violent behavior and trigger an alarm to alert others to intervene or prevent the action.	

AI Motorized Pro Bullet Network Camera








Event	One-Click Disarm	Support					
	Basic Event	Motion Detection, Tamper Detection, Audio Alarm, External Input, External Output etc.					
	Exception	Network Disconnection, IP Address Conflict, Record Failed, SD Card Full, SD Card Uninitialized, SD Card Error, No SD Card, etc.					
	Event Action	FTP Upload Record, SMTP Upload Record, SD Card Record, Snapshot, External Output, Play Audio, SIP Phone, HTTP Notification, etc.					
System	Watermark	Support					
	Storage	Support Micro SD/SDHC/SDXC Card Local Storage, up to 1TB					
	SIP/VoIP Support	Yes, Voice & Video-over-IP					
	System Compatibility	ONVIF Profile G & M & S & T, One API					
General	Working Temperature	-40°C~60°C					
	Working Humidity	0~95% RH (Non-condensing)					
	Power Supply	PoE (802.3af) / DC 10V~DC 28V					
	Power Consumption	<table border="0"> <tr> <td>Min.: 3.2W (DC), 4.2W (PoE)</td> <td>Min.: 4W (DC), 5W (PoE)</td> </tr> <tr> <td>24 Hour Average: 4.7W (DC), 5.9W (PoE)</td> <td>24 Hour Average: 5.5W (DC), 6.7W (PoE)</td> </tr> <tr> <td>Max.: 7.6W (DC), 9.2W (PoE)</td> <td>Max.: 9.1W (DC), 10.8W (PoE)</td> </tr> </table>	Min.: 3.2W (DC), 4.2W (PoE)	Min.: 4W (DC), 5W (PoE)	24 Hour Average: 4.7W (DC), 5.9W (PoE)	24 Hour Average: 5.5W (DC), 6.7W (PoE)	Max.: 7.6W (DC), 9.2W (PoE)
Min.: 3.2W (DC), 4.2W (PoE)	Min.: 4W (DC), 5W (PoE)						
24 Hour Average: 4.7W (DC), 5.9W (PoE)	24 Hour Average: 5.5W (DC), 6.7W (PoE)						
Max.: 7.6W (DC), 9.2W (PoE)	Max.: 9.1W (DC), 10.8W (PoE)						
Surge Protection	4KV						
Net Weight	Approx. 1.3kg						
Gross Weight	Approx. 2.1kg						
Dimensions	134mm X 126mm X 285mm						
Warranty	3 Years / 5 Years (Optional)						
Certifications	EMC	CE-EMC (EN 55032, EN 55035), FCC (PART 15B)					
	Safety	CE-LVD (EN IEC 62368-1)					
	Environment	CE-ROHS (Directive (EU) 2015/863 amending 2011/65/EU)					
	Protection	IP67					

*The tested results may vary due to environmental conditions and device differences.

AI Motorized Pro Bullet Network Camera



Structure Diagrams



Units: mm

Accessories Support

